



AXCL BRAKE FLUID DOT 3

PRODUCT DESCRIPTION

AXCL Brake Fluid is a high-quality brake fluid blended from glycol ethers and Polyglycols. It is formulated to contain oxidation and corrosion inhibitors to enhance its chemical stability

SPECIFICATION

- SAE J 1703
- ISO 4925
- FMVSS 116 DOT 3
- NF R12-640

BENEFITS AND ADVANTAGES

- High boiling point to prevent vapor forming in brake systems
- Firm braking pressure in all operating conditions
- Excellent chemical stability
- Protects metals and rubbers used in brake and hydraulic systems

SPECIFICATION & TECHNICAL PARAMETER

N#	Test	DOT-4
1.	Appearance	Bright & Clear
2.	Color	Neutral
3.	Kin. Viscosity @ 100 °C	1.55 min.
4.	Kin. Viscosity @ -20 °C	1500 max
5.	ERBP °C min	205 min.
6.	WERBP °C min	140 min.
7.	pH	8.6
8.	Density @ 20 °C g/cm3	1.025

**Technical data provided here is for reference only. Minor variations in product typical test data are to be expected.*

***All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative.*